Built Sept., 1954, American Locomotive Co.
Builder's No. 80743,80475

Diesel Electric Road Switching Locomotive No. 197
ex DC-23
192




RADIO EQUIPPED 1960

GENERAL DATA - MU Connections - Front and Back — Dynamic Braking - 650 Amps. Max. 33000# & 22 MPH

| | | | |
|---|---|---|---|
| 1. | Weight - Working Order | 260,000 lbs. | |
| 2. | Horsepower | 1600 | |
| 3. | Ratio of Gears | 74-18 | |
| 4. | Maximum Speed (Overspeed setting) | 65 M.P.H. | |
| | ENGINE | | |
| 5. | Type-4 Cycle, V Type, Series 244G, Turbo Superch'd. Alco | | |
| 6. | Cylinders - Bore and Stroke | 12- 9" dia. x 10½" | |
| 7. | Speed - Idling 350 R.P.M. at Rated H.P. 1000 R.P.M. | | |
| 8. | Supercharger-Alco-510D, Eng. Air In. Filter Oil Bath-Air Maze 3 | | |
| 9. | Governor G.E. Type 17-MG6D1 Electro-Hydraulic | | |
| | ELECTRICAL | | |
| 10. | 1 - G.E. Main Generator Type 5GT581A1 Cont. Rat. 2170 Amps. | | |
| 11. | 1 - G.E. Aux. Generator Type 5GY-27A3 12 KW, 75 Volts DC | | |
| 12. | 1 - G.E. Exciter Type 5-AM-808-A3, 9KW, 100V, 2400 RPM | | |
| 13. | 4 - G.E. Tract. Motors Type 5GE-752-E1, 1085 Amps. Cont. DC | | |
| 14. | 1 - G.E. Radiator Fan Aphonic Type 5GDY32A1 75 Volts DC | | |
| 15. | 1 - G.E. Fuel Pump Type 5DC76AB-286A, 1 H.P. 75 Volts DC | | |
| 16. | Control Equipment-GE Type P, Overspeed with Time Delay | | |
| 17. | Multiple Control Cable 60 Inch Length, 27 Wires | | |
| 18. | Batteries 32 Cells, 64 Volt, Exide MV-25-D | | |
| 19. | Lighting Circuit | 75 Volts | |
| 20. | Headlight - 2 Pyle-National Twin-Sealed Beam 200W, 30V | | |
| | TRACTIVE POWER | | |
| 21. | Starting at 25% adhesion | 65,000 lbs. | |
| 22. | 10 M.P.H. | 49,000 lbs. | |
| 23. | 15 M.P.H. | 33,500 lbs. | |
| 24. | 20 M.P.H. | 25,000 lbs. | |
| 25. | 25 M.P.H. | 20,000 lbs. | |
| 26. | 30 M.P.H. | 16,500 lbs. | |
| 27. | Continuous Rating | 52,500 lbs. at 8.0 M.P.H. | |

| | | |
|---|---|---|
| | CAPACITY | |
| 28. | Fuel Oil 2000 Gals. (1 Tank) | Lubricating Oil 200 Gals. |
| 29. | Cooling Water - 250 Gallons | Sand - 28 cu. ft. |
| | AIR BRAKE J-16 Red. Valve | |
| 30. | Schedule | 24 RL W.A.B.Co. |
| 31. | Brake Power @ 30 lbs. cylinder pressure | 106,800 lbs. |
| 32. | Air Compressor | Westinghouse 3 CDH |
| 33. | Air Compressor Capacity at full engine speed | 306 CFM |
| 34. | Reservoir Capacity | 60,650 cu. in. |
| 35. | Feed Valve - D-24-B | Relayair Valve RA-24-C |
| 36. | Deadman Control-Foot Pedal - Breakintwo Protection Valve | |
| 37. | Handbrake Arax, | Reservoir Drain Valves Prime |
| | MISCELLANEOUS | |
| 38. | Fire Extinguishers 2¾" Ansul in cab, | 2 - 30-lb. Ansul |
| 39. | Sanders - 8 Graham-White | Windshield Wipers - Sprague |
| 40. | Horns - 2 Leslie S5T Chime (#192 Nathan M5 Nos) | Bell Ringer Prime |
| 41. | Speed Recorder | Barco DP, 0-60 M.P.H. |
| 42. | Draft Gear - Miner RF-333 (Cushion) | Couplers A.A.R. Type "E" |
| 43. | ~~Steam Generator - 2750#/Hr. - Vapor-Clarkson CC-4685-84~~ | |
| 44. | ~~Water Capacity for Steam Generator~~ | ~~1200 Gals.~~ |
| | TRUCKS V-110 Cobra Brake Shoes | |
| 45. | Type | 4-wheel Swivel Swing Motion Pedestal Type |
| 46. | Axles | 6½" x 12" Journals for Hyatt Roller Bearings |
| 47. | Wheels | 40" M.W. Rolled Steel |
| 48. | Brake Cylinders | 8 - 10" dia. x 8" W.A.B.Co. |
| 49. | Side Bearings | Plain Steel - Hardened |
| | LIMITING DIMENSIONS | |
| 50. | Maximum Length Coupled | 55' - 5-3/4" |
| 51. | Maximum Height | 15' - 3-11/16" |
| 52. | Maximum degree of curvature 57 degrees - Coupled 30 deg. | |

16