



GENERAL		DRAFT (Continued)	
1. Capacity - level	1830 cu.ft.	Nominal	110,000 lbs.
2. Load Limit			127,700 "
3. Light weight			41,300 "
4. Maximum load on rails			169,000 lbs.
BODY		AIR BRAKE	
5. Framing - Underframe steel	Superstructure Steel	16. Brake schedule	W.A.B. KD-1012
6. Floor 3/8" steel, Sheathing 1/4"	St. Pockets None	17. Brake power	28,744 lbs. 69%
DOORS		HAND BRAKE	
7. Door operating device	Wine	18. Operating device	Ajax 22" Wheel
8. Door opening	2' 5-5/8" x 3' 4-3/4"	TRUCKS	
ROOF		19. Frame	C.S. Double Truss
9. Make	None	20. Dead lever fulcrum	Wine Brake Balancer
10. Carlines	None	21. Side bearing	Stucki All Steel
DRAFT		22. Lateral Motion Device	None
11. Draft gear	Miner A-22-XB	23. Snubbers	None
12. Draft attachments	Farlow two-key	24. Axles	A.A.R. 5 1/2" x 10"
13. Couplers	A.A.P. "D"	25. Wheels	Cast Iron A.A.R. 33"
		26. Brake beam auxiliary support	Single Economy - Creco
		27. Train length, coupled	34' - 9"