



GENERAL		DRAFT (Continued)	
1. Capacity - level	3293 cu.ft. Nominal 100,000 lbs.	14. Coupler Centering Device	None
2. Load limit	121,635 "	15. Coupler Uncoupling Device	"Imperial Rotary"
3. Light Weight	47,365 "	AIR BRAKE	
4. Maximum load on rails	169,000 "	16. Brake Schedule	"AB" 10" x 12"
BODY		17. Brake Power	31,020 lbs. 65%
5. Framing-Underframe	Duryea Steel Superstructure Steel	HAND BRAKE	
6. Floor	2-3/8" YP, Sheathing .10 Steel, St.Pockets-None	18. Operating Device	Ajax 22" Wheel
DOORS		TRUCKS	
7. Door operating device	Camel Lift Type	19. Frame	C.S. Double Truss
8. Door opening	6' 0" x 6' - 8-1/16"	20. Dead lever fulcrum	Wine Brake Balancer
ROOF		21. Side Bearing	Wine Self Center, Roller Type
9. Make	Chicago-Hutchins	22. Lateral Motion Device	None
10. Carlines	Steel	23. Snubber	Symington Type SBR
DRAFT		24. Axles	A.A.R. 5 1/2" x 10"
	Duryea Cushion	25. Wheels	Cast Iron A.A.R. 33" Wheel