



GENERAL		DRAFT (Continued)	
1. Capacity - level	1600 cu.ft.	Nominal	140,000 lbs.
2. Load limit			141,000 "
3. Light weight			69,000 "
4. Maximum load on rails			210,000 "
BODY		AIR BRAKE	
5. Framing - Underframe Steel	Superstructure Steel	14. Coupler centering device	Union
6. Flooring Steel, Siding Steel, Stake Pockets 4" x 4"		15. Coupler uncoupling device	Carmer
DOORS		HAND BRAKE	
7. Door operating device	None	16. Brake schedule	W.A.B. "AB" 10" x 12"
8. Door opening	None	17. Brake power	41,484 lbs. 60%
ROOF		TRUCKS	
9. Make	None	18. Operating Device	Ajax 22" wheel
10. Carlines	None	19. Frame	Cast Steel
DRAFT		20. Dead Lever Fulcrum	Wine Brake Balancer
11. Draft gear	Miner A-79-X	21. Side Bearing	Stucki All Steel
12. Draft Attachments	Farlow Twin key	22. Lateral Motion Device	Barber
13. Couplers	Symington Swivel Butt A.A.R. "D" Head	23. Snubber	Half Simplex; Half Miner Class C-2-XB
		24. Axles	A.A.R. 6" x 11"
		25. Wheels	Cast Iron A.A.R.33"
		26. Brake beam auxiliary support	Single Economy Creco
		27. Train length, coupled	66' 0 1/2"