



GENERAL		DRAFT (Continued)	
1. Capacity - Level 1892 cu.ft.	Nominal 140,000 lbs.	14. Coupler cushion and positioning device	S.R.E.M.Co.
2. Load limit	157,800 "	15. Coupler uncoupling device	Imperial Rotary
3. Light Weight	52,200 "	AIR BRAKE	
4. Maximum load on rails	210,000 "	16. Brake schedule	W.A.B. Co. AB 10" x 12"
BODY		17. Brake power	38,118 lbs. 75%
5. Framing-Underframe Duryea Steel, Superstructure Steel		HAND BRAKE	
6. Floor 1/4" Steel	Steel Sheathing #7 USS Ga.	18. Operating device	Ajax 22" Wheel
DOORS		TRUCKS	
7. Door operating device	Enterprise	19. Frame	2-1/2" Spring travel - A3 Ride Control A.S.F.
8. Door opening	4 - 13" x 24"	20. Brake balancer	Wine
ROOF		21. Side bearing	Stucki
9. Make	No. 13 USS gauge galv.o.b. S.R.E.Co.	22. Spring plank	None
10. Hatch opening	10 - 36" x 36"	23. Snubbers	Bolster friction blocks - A.S.F.
DRAFT		24. Axles	6" x 11"
11. Draft gear	Double spring, Cushioned, Duryea	25. Wheels	One-wear wrot steel 33"
12. Draft Key A.A.R.	Retainer lock I.R.E.Co.	26. Brake beam support and safety device	Creco 4-point
13. Coupler	A.A.R. Type "E" 6-1/4" x 8"	27. Train length coupled	39' 2-3/4"