



GENERAL		DRAFT (Continued)	
1. Capacity - Level	2622 cu.ft.	Nominal	140,000 lbs.
2. Load Limit			155,900 "
3. Light Weight			54,100 "
4. Maximum Load on Rails			210,000 lbs.
BODY		16. Coupler Centering Device with Height Adjust. SREX	
5. Underframe - Center Sill	AAR Z-26, 51.2 lbs. Steel	17. Coupler Uncoupling Device "Standard" SREX	
6. Slope Floor, Hop., Crossridge, Long. Hd.,	3/8" Mayari R St.	BRAKES	
7. Sides and Ends	1/4" Mayari R Steel	18. Brake Schedule	W.A.B.Co. "AB" 10" x
8. Bulb Angle - Sides and Ends	5" x 4-1/2" x 7/16"	19. Brake Power	39,585 lbs.
9. Hopper Door Frames and Fixtures	Wine	20. Hand Brake - AAR Approved	250 AJAX 250 KLAS
10. Hopper Door Opening	6 - 25-7/8" x 36"	21. Brake Regulator	Type "MS" C. M. O'Bo
11. Side and End Ladders	"Safe Grip" Wine	TRUCKS 2-1/2" Spring Travel, Stabilized S-2-A Bar	
DRAFT		22. Frames - Narrow Pedestal Type	Cast Steel
12. Draft Gear	RF-333 Miner	23. Brake Levers & Bottom Connectors	Pittsburgh Forging
13. Draft Key - AAR 6" x 1-1/2"	Retainer Lock I.R.E.Co.	24. Side Bearings	Stu
14. Coupler - Bottom Operated	AAR Type "E" 6-1/4" x 8"	25. Roller Bearings with Heat Indicators	"AP" 6" x 11" Tim
15. Coupler Yoke	Vertical Type Y-40 Cast Steel AAR	26. Snubbers	Bolster Friction Blo
		27. Brake Beams	"Unit" Type Cr
		28. Axles - A.A.R. 6" x 11"	Wheels - MW Wrot Steel
		29. Bearing Lubrication	Taxaco Grease No.
		30. Train Length Coupled	44'