



LAHT 15,500 lbs.

GENERAL		18. Coupler Uncoupling Device "Standard" SREM Co.	
1. Capacity - Level 2603 cu.ft.	Nominal 140,000 lbs.	19. Brake Schedule	W.A.B.Co. "AB" 10" x 12"
2. Load Limit	153,700 lbs.	20. Brake Power	41220 lbs. 73%
3. Light Weight 72391-395 - 56,000 72396-400 - 56,220	72001 72390 56,300 lbs.	21. Brake Cylinder Release Valve	W.A.B.Co. Type QRR
4. Maximum Load on Rails	210,000 lbs.	22. Hand Brake	72001-72200 - Ajax 72201-72400 - Universal
5. Underframe - Center Sill 2-26 @ 51.2 lbs.	Steel	23. Automatic Brake Regulator	72001-72200 - SAB 72201-72400 - Elcon
6. Inter.Slope, Hop., Crossridge, Long.Hd.3/8" Mayari "R"		24. Trucks - 2 1/2" Spring Travel, Stabilized	S-2-A0 Barber
7. Sides and Ends 1/4" Mayari "R", 26 Stakes 1/4" C.B.S.		25. Frames - Narrow Pedestal Type	Cast Steel
8. End Floor Sheet	5/16" Mayari "R"	26. Brake Levers and Bottom Connectors	Pittsburgh Forg. Co.
9. Bulb Angle - Sides & Ends 5" x 4 1/2" x 7/16" - 19.1 lbs.		27. Bearings	72001-72390 Roller Bearings "AP" Timken 72391-72395 Cartridge Kar-Go - Allison 72396-72400 Cartridge ABSCo.
10. Hopper Door Frames - Wine, Door fixtures 300 Wine 100 Keystone		28. Brake Beams	AAR #18 Unit Type
11. Hopper Door Openings	6 - 25-3/4" x 35-3/4"	29. Axles AAR D-6D 6" x 11",	Wheels MW Wrot Steel D-33
12. Side and End Ladders "Safe Grip"	Wine	30. Bearing Lubrication	Timken - AAR "RB" Grease
13. Draft Gear 72001-72350 A-22-XL Miner 72351-72400 Mark 40 Card.-West.		31. Side Bearings	Stucki
14. Draft Key - AAR 6" x 1 1/2"	Retainer Lock I.R.E.Co.	32. Train Length Coupled	43' - 7"
15. Coupler - Bottom Operated	AAR Type "E", 6 1/4" x 8"		Allison and ABSCo. - AAR Car Oil
16. Coupler Yoke	Vertical Type Y-40, Cast Steel AAR		
17. Coupler Centering Device with Height Adj.	None		