



CARS NOS 85141-85150 EQUIPPED WITH BRAKE 'X'

GENERAL			18. Coupler Uncoupling Device "Standard Rotary" SREMO.
1. Capacity - Level 2550 cu.ft.	Nominal	200,000 lbs.	19. Brake Schedule WABCO "AB" 10" x 12"
2. Load Limit		203,100 lbs.	20. Brake Power (85001-85140) 25068# 9.53% Gross Rail Load
3. Light Weight		59,900 lbs.	21. Brake Shoes (85001-85140) Cobra V-139 WABCO
4. Maximum Load on Rails		263,000 lbs.	22. Brake Regulator (85001-85140) Ellcon-National
5. Center Sills Z-26	51.2 lbs. Cast Steel End Sections ASX		23. Brake Cylinder Release Valve "QRB" WABCO
6. Floor, Hood, Crossridge, Hopper Chutes, Doors	5/8" Mayari B		24. Hand Brake Miner Bell Crank AAR No. 63
7. Sides & Ends	1/4" Mayari R, Inside Braces Cast St. Scullin		25. Trucks 2-1/2" Spring Travel, Stabilized S-2-A0 Barber
8. Bulb Angle - Sides & Ends	5"x 4-1/2" x 7/16" - 19.1 lbs.		26. Frames Narrow Pedestal Type Cast Steel AAR
9. Bulb Angle Reinforcement	4" x 4" x 1/2" Angle		27. Brakes Levers and Bottom Connectors Schaefer
10. Hopper Door Frames and Fixtures	Wine		28. Side Bearings No. 688 double roller A. Stuckl
11. Hopper Door Openings	6 - 25-3/4" x 35-3/4"		29. Roller Bearings with Heat Indicators AP 6 1/2" x 12" Timken
12. Side and End Ladders	"Safe Grip" Wine		30. Brake Beams (85001-85140) AAR No. 18 Unit Buffalo
13. Draft Gear	A-22-XL Miner		31. Wheels 85001-85140 AAR K-36 MW Heat Treated Class CR
14. Draft Key	AAR 6" x 1 1/2" Retainer Lock IHeco.		32. 85141-85150 AAR H-36 1-W Heat Treated Class CR
15. Coupler	AAR Type E, 6-1/4" x 8" Bottom Operated		33. Axles AAR D-6-D, 6 1/2" x 12", AAR Spec. M-126-56 Grade F M&T
16. Coupler Yoke	Vertical Type B-Y40 Cast Steel AAR		34. Bearing Lubrication AAR RB Grease
17. Coupler Centering Device	None		35. Train Length Coupled 45' - 6-1/2"