



GENERAL		DRAFT (Continued)	
1. Capacity - level 1830 cu.ft.	Nominal 110,000 lbs.	14. Coupler centering device	None
2. Load Limit	127,700 "	15. Coupler uncoupling device	Imperial "B"
3. Light weight	41,300 "	AIR BRAKE	
4. Maximum load on rails	169,000 lbs.	16. Brake schedule	W.A.B. KD-1012
BODY		17. Brake power	28,744 lbs. 69%
5. Framing - Underframe steel	Superstructure Steel	HAND BRAKE	
6. Floor 3/8" steel, Sheathing 1/4"	St. Pockets None	18. Operating device	Ajax 22" Wheel
DOORS		TRUCKS	
7. Door operating device	Wine	19. Frame	C.S. Double Truss
8. Door opening	2' 5-5/8" x 3' 4-3/4"	20. Doad lever fulcrum	Wine Brake Balancer
ROOF		21. Side bearing	Stucki All Steel
9. Make	None	22. Lateral Motion Device	None
10. Carlines	None	23. Snubbers	None
DRAFT		24. Axles	A.A.R. 5 1/2" x 10"
11. Draft gear	Minor A-22-XB	25. Wheels	Cast Iron A.A.R. 33"
12. Draft attachments			