



Rear Window Glass 16<sup>3</sup>/<sub>4</sub>" x 20<sup>3</sup>/<sub>4</sub>" Safety Plate  
 Cab Heater - Kysor SB

Light Weight 169,500 lbs.

1. Total Weight in working order	196,300 lbs.	12. Boom - 50 Ft. Lattice Type with 10 Ft. Insert - 60 Ft.	
2. Diesel Engines-General Motors - Ser. 6-71 Dst. D.E. Div.		13. Boom - Rotary Speed - maximum	6 RPM
Power Unit 1-Model 6082, 2 Cycle	No. 6A-56588	14. Boom Main Hoist Rad. 12'-50'	Max. Speed 210 FPM
Bore & Stroke 4-1/4" x 5" RPM 2000	H.P. 165	15. Cables with (Main Hoist 1-7/8" dia. (6x19)-120', 1-7/8" dia.-275 Ft. Lg.	
Generator Drive 1-Model 2043-B Ser. 2-71, 2 Cycle		60 Ft boom (Boom Hoist-2-1" dia (6x19) 125 Ft. Lg.	
Unit No. 2A-40968, Bore & Stroke 4 1/2" x 5", RPM 1800, 20 KW		16. Bucket-Clam Shell, General Purpose (1-1 1/2 Cu. Yd.) (1-5 Cu. Yd)	
3. Main Drive Allison Torque Conv. with HD Twin Disc Clutch for reversing		17. Capacity - Pounds	
4. Air Compressor - West. 5-YC-1-1 Belt driven Ser. 1729		50 Ft. Boom	Crane Free
5. Air Brakes	A 1, SWA-1012, KD-1012	Rad. 15 Ft.	52,700 lbs.
6. Electrical		" 16 1/2 "	80,000 lbs.
Generator Model 110C370, 32 Volt, Serial 1117	Delco	" 20 "	36,400 "
Generator for 45" Lift. Magnet, GM 240 V., 63 A., 20KW		" 25 "	27,500 "
Battery 4 - 8-volt, 165 Amperes	Deka	" 30 "	21,400 "
Lights - Cab 2 - 15 W., 2 - 100 W., Boom 2-75W		" 35 "	17,900 "
Alarm	Edwards Adaptabel	" 40 "	14,900 "
7. Diesel Engine Supplies	Power Unit	Generator Drive	
Lubricating Oil	7-1/4 Gals.	2-3/4 Gals.	
Water	8-3/4 "	8 "	
Fuel Oil	Capacity 147 Gallons		
8. Travel speed of crane with maximum load	7.5. MPH		
9. Draft Gears	Miner Twin Spring		
10. Trucks	8" x 11" with Cast Steel Frames		
11. Maximum Radius of Curvature	75 Ft.		