



Light Weight - 198,387 lbs.

Fire Extinguisher - 1, 20-lb. Ansul

1. Total Weight in working order	199,540 lbs.	12. Boom	50 Ft. Lattice Type with 10 ft. Insert
2. Diesel Engines - General Motors Series 71 Det.D.E.Div.		13. Boom Rotary Speed - maximum	4 RPM
Power Unit 1-Model 6032, 2 Cycle, Unit No. 6A-26978		14. Boom Main Hoist Rad. 12'-50'	Max. Speed 200 FPM
Bore & Stroke 4-1/4" x 5" RPM 2000 H.P. 165		15. Cables with (Main Hoist 1-1" dia. (6x19) - 390 Ft. Long	
Generator Drive 1-Model 2043-C, 2 Cycle, Unit No. 2A-18311		60 Ft. Boom (Boom Hoist 2-7/8" dia. (6x19) - 143 Ft. Long	
Bore & Stroke 4-1/2" x 5" RPM 1800 20 KW		16. Bucket - Clam Shell General Purpose Capy.	1 Cu. Yd.
3. Main Drive G.M. Torque Conv. with HD Twin Disc Clutch for Reversing		17. Capacity - Pounds	
4. Air Compressor-West. 4YC, 47 cfm belt driven Ser. 241562		50 Ft. Boom	Crane Free With Outriggers
5. Air Brakes S-3 Brake Valve, KD-10 x 12		Rad. 12 Ft.	100,000 lbs.
6. Electrical		" 15 "	54,500 lbs.
Generator - Model 1106870, 32V, 25A Ser.No. 341 Delco		" 20 "	37,700 "
Generator for 54" Lifting Magnet 240 V. D.C. 20KW		" 25 "	23,200 "
Battery 5- 6V-HD - 115 Amp.hr.		" 30 "	22,350 "
Lights Cab 4 - 50Watts On Boom 2 - 50 Watts		" 35 "	18,200 "
Alarm Edwards Adaptabel		" 40 "	15,250 "
7. Diesel Engine Supplies Power Unit Generator Drive		" 45 "	13,600 "
Lubricating Oil 7-1/4 Gals. 2-3/4 Gals.		" 50 "	11,650 "
Water 8-3/4 " 3 "		60 Ft. Boom	
Fuel Oil Capacity 137.5 "		Rad. 20 Ft.	36,800 lbs.
8. Travel speed of crane with maximum load 7.5 MPH		" 30 "	21,450 "
9. Draft Gears - National M-17 Couplers-AAR 6-1/4" x 8"		" 40 "	14,850 "
10. Truck 6" x 11" with Cast Steel Side Frames		" 50 "	10,750 "
		" 60 "	8,750 "