



1. Total Weight in working order	385,000 lbs.	18. Tractive Effort	24000 lbs., 2 DRIVERS, DRAWBAR PULL 16600 lbs.
2. Diesel Engine - General Motors Series 6-71		14. Truck	6-wheel, Buckeye Steel Casting Co.
Power Unit - 1 Model 12107 Twin Six Serial No. 12A3923		15. Wheels	33" M.W. Steel
Bore and Stroke 4-1/4" x 5", RPM 2000	H.P. 330	16. Axles	6-1/2" x 12"
3. Main Drive - Allison Torque Converter with HD TWIN DISC CLUTCH		17. Fire Extinguishers	2 - 30 lb. Ansul
4. Air Compressor - 2 West. 5-YCAL, 65 cfm, V-Belt Drive		18. Capacity - Pounds	
5. Air Brakes WABCO Automatic & Straight Air P2 Triple 60%		Main Hoist:	
6. Electrical Equipment		Radius Crane Free (With Wedges)	With All Outriggers
Generator - Model 117563, 52V, 1500W, Ser. No. 1203 Delco		17-1/2 Ft.	80,000 lbs. 500,000 lbs.
Battery - 4 - 8-volt, 165 amps. Deka		20 "	65,000 " 380,000 "
Lights 4-50W, Front of Cab 2-250W, 2-4-way side socket		22-1/2 "	54,000 " 320,000 "
Back of cab 1 - TSIC-1150W, Boom - 3 - 100W		25 "	46,000 " 270,000 "
Immersion Heater - 115V AC, 2000 W, G.F. Calrod Unit		28 "	38,000 " 220,000 "
Diesel Engine Alarm Adantabel <small>HIGH WATER TEMPERATURE LOW LUBE OIL</small> Edwards		32 "	28,000 " 170,000 "
7. Cranes Supplies Fuel Oil 234 gals., LUBE OIL 16 GALS., WATER 34 GALS.		35 "	22,000 " 130,000 "
8. Boom - Structural & Cast Steel - All Welded Construction		Auxiliary Hoist:	
Main Hoist Radius 17-1/2' - 36'	Max. Speed 12.6 FPM	25 ft.	53,000 lbs. 120,000 lbs.
Aux. Hoist Radius 25' - 47'	" " 154.0 FPM	28 "	44,000 " 120,000 "
Rotary Speed (Light) Maximum	1.8 RPM	32 "	35,000 " 120,000 "
9. Propelling Speed, Maximum	3.4 MPH	35 "	31,500 " 120,000 "
10. Cables - Main 1 1/4" x 800', Aux. 1-1/8" x 300', Jib 1-1/4" x 346'		40 "	26,000 " 110,000 "
11. Draft Gear	NY-11-E Cardwell-Westinghouse	45 "	21,000 " 100,000 "