



1. GENERAL - Light Weight	80,200 lbs.	24. Screens	Upper deck
2. Capacity, Max.	65,800 lbs.	26. GLASS - Lower sash, none	Upper sash none
3. Length over all, coupled	62' 4"	26. Doors, side 3/16" crystal	Mirrors, none
4. " " end sills	58' 9 1/2"	27. SEATS	1-Wood of air
5. " inside	58' 0"	28. Upholstery	None
6. " between truck centers	42' 9 1/2"	29. WATER - Supply, None	Coolers, Galvanized iron
7. " truck wheel base	8' 0"	30. HEATING - System, Cold	Type, Direct
8. Width over all, at eaves	10' 1"	31. LIGHTING - System,	Electric
9. " inside	8' 11 1/2"	32. MAIL - Apartment	Fixtures, None
10. Height, track to roof at center	14' 1 1/4"	33. BRAKES - Power, 73600 lbs., 82%	Schedule, P.L. 1412
11. " " eaves	11' 6 1/2"	34. TRUCKS - Frames	Cast steel
12. Highest point of car, lamp jack	14' 6"	35. Side Bearings	Barber
13. BODY - Underframe, steel	Superstructure, Wood	36. Axles	A.R.A. 5" x 9"
14. Sheathing, poplar	Roof, #8 Canvas	37. Journal boxes	A.R.A. 5" x 9"
15. Insulation	None	38. Wheels, per truck	4 - 36" Steel
16. Inside finish	Poplar painted	39. Brake beams	High speed - 24,000 lbs.
17. Flooring	Double - Yellow Pine & Maple		
18. Ventilators	Deck sash		
19. COUPLERS, Janney	Draw Bar, 3-stem		
20. Draft gear, Sessions "C"	Buffer, Standard "D3"		
21. Trap doors	None		
22. WINDOWS - Sash	None		
23. Shades	None	* See list of lighting equipment.	