



AIR CONDITIONED

1. GENERAL - Light Weight	147,600 lbs.	24. Screens	None
2. Capacity	20 Passengers	25. GLASS - Lower sash 3/16" crystal Upper sash, Opalescent	
3. Length over all, coupled	75' 9 1/2"	26. Doors, 3/16" Crystal	Mirrors (Yes)
4. " " " end sills	67' 9 1/2"	27. SEATS - Make Barney & Smith	Type, Miscellaneous
5. " " " inside	67' 0"	28. Upholstery - Materials, leather	Style, Spanish
6. " " " between truck centers	51' 6"	29. WATER - Supply, Air Pressure	Coolers, None
7. " " " truck wheel base	10' 6"	30. HEATING - System, Chicago	Type, Vapor
8. Width over all, at eaves	10' 4"	31. *LIGHTING - System, U.S.L.	Batteries, Edison
9. " " " inside	8' 9"	32. MAIL - Apartment	None
10. Height, track to roof at center	15' 10 1/2"	33. BRAKES - Power 125,000 lbs.	85% Schedule, FM-1812
11. " " " eaves	11' 2 1/4"	34. TRUCKS - Frames	Cast Steel
12. Highest point of car, over antenna	14' 9"	35. Side bearings	Plair
13. BODY - Underframe, Steel	Superstructure, Wood	36. Axles	A.A.R. 5" x 9"
14. Sheathing, Poplar	Roof, #8 Canvas	37. Journal boxes	A.A.R. 5" x 9"
15. Insulation	SALAMANDER	38. Wheels, per truck	6 - 36" steel
16. Inside finish	Mahogany	39. Brake beams	High Speed Special - 28,000 lbs.
17. Flooring	Double Yellow Pine	40. AIR CONDITIONING	A.C.F. Ice Activated
18. Ventilators	10 - Garland	41. AIR DISTRIBUTION	Outside Duct
19. COUPLERS, Janney	Draw Bar, 3-Stub	42. GENEMOTOR	Gen. 10 KW - AC Motor 15 H.P.
20. Draft gear	Minor Tandem Buffer, Standard D-3	43. Drive	Spicer
21. Trap doors	National		
22. WINDOWS - Sash, Double			
23. Shades - material, Pantasote		* See list of lighting equipment	