



1. GENERAL - Light weight	114,100 lbs.	24. Screens	Upper Deck
2. Capacity - 48 Passengers.	20,000 lbs.	25. GLASS - Lower sash, 1/8" crystal	Upper sash, None
3. Length over all, coupled		26. Doors, 3/16" Crystal	Mirrors, 1 - 1/2" x 12" x 12"
4. " " end sills	70' 3 1/2"	27. SEATS - Make, Heywood & Wakefield.	Type, #85 A.C.F.
5. " " inside	69' 7 1/2"	28. Upholstery - Material, Fabricord	Style, "X"
6. " " between truck centers	53' 5 1/2"	29. WATER - Supply, Gravity	Coolers, Geissel
7. " " truck wheel base	8' 0"	30. HEATING - System, Chicago	Type, Vapor
8. Width over all, at eaves	10' 1"	31. LIGHTING - System, U.S.L.	Batteries, Edison
9. " " inside	8' 2 1/2"	32. MAIL - Apartment	None
10. Height, track to roof at center	13' 3 1/2"	33. BRAKES - Power 107,030 lbs., 84%	Schaffle, LN-1612
11. " " " eaves	10' 11 1/2"	34. TRUCKS - Frames	Cast steel
12. Highest point of car, roof	13' 8 1/2"	35. Side bearings	Stucki
13. BODY - Underframe, Steel	Superstructure, Steel	36. Axles	A.R.A. 5 1/2" x 10"
14. Sheathing, steel plate	Roof, Steel	37. Journal boxes	A.R.A. 5 1/2" x 12"
15. Insulation	Salamander	38. Wheels, per truck	4 - 36" steel
16. Inside finish	Steel, Painted	39. Brakes	A.E.Co, Clasp
17. Flooring	Ghanarch - Flexolith		
18. Ventilators	Midge - Fearless		
19. COUPLERS, Pitt	Draw Bar, Single Stem		
20. Draft gear, Westinghouse D-3, Buffer, Pullman spring			
21. Trap doors	Universal		
22. WINDOWS - Sash, single	Forsythe		
23. Shades - Material, Fantasote, Fixa, Cur.Sup.Co. # 8		* See list of lighting equipment	