



built
10/1906

1. GENERAL - Light Weight	78,400 lbs.	24. Boreens	Deck Mast
2. Capacity	70 Passengers	25. GLASS - Lower sash, double thick Upper sash, Opalescent	
3. Length over all, coupled	68' 0"	26. Doors, $\frac{1}{2}$ " Plate	Mirrors None
4. " " and sills	60' 0"	27. SEATS - Lake, Hale & Kilbourn	Type, #97
5. " inside	59' 4 $\frac{1}{2}$ "	28. Upholstery - Material, plush	Style, Chases "M"
6. " between truck centers	42' 0"	29. WATER - Supply, None	Coilers, Geissel
7. " truck wheel base	8' 0"	30. HEATING - System, Cold	Type, Direct
8. Width over all, at eaves	10' 0"	31. LIGHTING - System, Gas	Tanks, 2 - 9' 0"
9. " inside	8' 10 $\frac{1}{2}$ "	32. WATL - Apartment	None
10. Height, truck to roof at center	14' 2 $\frac{1}{2}$ "	33. BRAKES - Power 52,560 lbs.	74% 12-1412
11. " " eaves	11' 2 $\frac{1}{2}$ "	34. TRUCKS - Frames	
12. Highest point of car, lamp jacks	14' 6"	35. Side Bearings	Woods #70
13. BODY - Underframe, Wood	Superstructure, Wood	36. Axles	A.R.A. 5" x 8"
14. Sheathing, poplar	Roof, #8 Canvas	37. Journal boxes	A.R.A. 5" x 9"
15. Insulation	None	38. Wheels, per truck	4 - 36" Steel
16. Inside finish	Golden, Oak	39. Brake beams	High speed - 24,000 lbs.
17. Flooring	Double - Yellow Pine		
18. Ventilators	Leak Sash		
19. COUPLERS, Janney	Draw Bar, 3-sten		
20. Draft gear, 6 $\frac{1}{2}$ " x 8" spring.	Buffer, Standard "A"		
21. Trap doors	Ordinary hand lift		
22. WINDOWS - Sash, Single	Ordinary lock		
23. Shades - Material, Pantasote	Fixtures, Forsythe		
			• See list of lighting equipment